

Technical

| Specifications | Standards | Secura | |
|-------------------------------------|---|--|------------------------------|
| Type of Floorcovering | EN 653 EN ISO 26986 | Heterogeneous Heterogeneous | |
| Product Enhancement | | PUR | |
| Gauge | EN 428 EN ISO 24346 | 3.0mm | |
| Wear Layer | EN 429 EN ISO 24340 | 0.35mm | |
| Performance Classification | EN 685 EN ISO 10874 | 23, 32, 41 | |
| Roll Size | EN 427 EN ISO 24341 | 2m x 25m = 50m ² 3m x 25m = 75m ² | 4m x 25m = 100m ² |
| Total Weight | EN 430 EN ISO 23997 | 1,780g/m ² | |
| Acoustic Impact Sound Reduction | EN ISO 10140-3 (EN ISO 140-8) | 19dB | |
| Residual Indentation | EN 433 EN ISO 24343-1 | ≤ 0.2mm | |
| Abrasion Resistance | EN 649 | Group T | |
| Dimensional Stability | EN 434 EN ISO 23999 | ≤ 0.40% | |
| Behaviour to Fire | EN 13501-1 | Bfl | |
| Slip Resistance | DIN 51130 EN 13893 | R10* Class DS (Dry Condition) | |
| Light Fastness | ISO 105-B02(Method 3) | ≥ 6 | |
| Resistance to Chemicals | EN 423 (ASTM F 1303-99) | Excellent | |
| Underfloor Heating Suitability | ISO 8302 | Suitable (Max 27°C) | |
| Castor Chair Suitability | ISO 4918 | Pass | |
| VOC Test | Indoor Air Comfort Gold AgBB | Approved Very low emissions | |
| Electrical Behaviour (body voltage) | EN 1815 | This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is requirement to dissipate the electrostatic charge, see the Polyflor ESD product range. | |
| Hygiene | This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection. | | |
| Environmentally Preferable Flooring | Polyflor Secura PUR achieves a BRE Global Environmental A Rating (Generic) in major use areas such as education and healthcare. Polyflor Secura PUR is 100% recyclable. EN 15804 Environmental Product Declaration is available upon request, and a full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment . | | |

*for commercial installations that require sustainable wet slip resistance, refer to the Polysafe ranges.





Environmental: Polyflor have demonstrated a high level of commitment over the years to producing high quality floorcovering, whilst minimising our impact on the environment without compromising the performance benefits of our products.

There can be few materials better suited to recycling than vinyl flooring. Secura is 100% recyclable, and can be recycled without losing any of its performance properties. Polyflor continually works on developing new products and technologies, and constantly evaluates production methods to further minimise our impact on the environment.



VOC EMISSIONS:

Indoor Air Comfort GOLD - Approved
AgBB - Very low emissions
FloorScore - Certified product



Refer to BRE Global ratings on
www.greenbooklive.com

For further details on Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance log onto
www.polyflor.com/environment



Guarantee

The Secura collection of luxury vinyl sheet flooring has been developed to meet the highest technical specification of its type. Ideal for all areas of the home, the products ensure high performance and optimum style. In addition, Secura is suitable for moderate commercial applications such as light traffic areas within hotels, conference rooms and small offices. Compared with many natural flooring options, Secura will under normal conditions resist household stains, will not crack, chip or splinter. The manufacturers of Secura are confident that their high quality products will provide many years of valuable service. All products purchased from the range are guaranteed for 20 years in domestic home installations against normal wear and tear in the recommended environment, provided that they have been fitted correctly and maintained in accordance with the manufacturer's instructions. In order to make a claim, customers must apply in writing indicating where the flooring was purchased and provide satisfactory proof of purchase. This guarantee only applies in the event of visible wearing out of the decorative pattern on the surface within 20 years of purchase, providing the flooring has been subject to normal usage in the recommended environment. It does not cover general misuse. Full terms and conditions of the guarantee are available on request from your flooring wholesaler or Polyflor Ltd.